



High Security (Double Ball Locking) Padlocks

Series Y - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
YT5*	9.53mm	19.05mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL
YG1	9.53mm	28.58mm	20.64mm	50.8mm	BRASS
YG2	9.53mm	28.58mm	20.64mm	50.8mm	HARDENED STEEL
YG3	9.53mm	28.58mm	20.64mm	50.8mm	STAINLESS STEEL
YG5*	9.53mm	28.58mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL
Y45*	9.53mm	38.1mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL
Y61	9.53mm	50.8mm	20.64mm	50.8mm	BRASS
Y62	9.53mm	50.8mm	20.64mm	50.8mm	HARDENED STEEL
Y63	9.53mm	50.8mm	20.64mm	50.8mm	STAINLESS STEEL
Y65*	9.53mm	50.8mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL
Y71	9.53mm	76.2mm	20.64mm	50.8mm	BRASS
Y72	9.53mm	76.2mm	20.64mm	50.8mm	HARDENED STEEL
Y73	9.53mm	76.2mm	20.64mm	50.8mm	STAINLESS STEEL
Y92	9.53mm	127mm	20.64mm	50.8mm	HARDENED STEEL

\* Meets or exceeds grade 6 of the ASTM F883 standards for cutting  
Key-retaining feature available for all models in this section.

**Wilson Bohannon Lock Company**

621 Buckeye Street • Marion, OH 43302 • [www.padlocks.com](http://www.padlocks.com)  
T: 800-382-3639 • F: 740-383-1653 • [wbc@padlocks.com](mailto:wbc@padlocks.com)