



High Security (Double Ball Locking) Padlocks

**Series Y - Model Comparison**

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
YT5*	3/8"	3/4"	53/64"	2"	HARDENED STAINLESS STEEL
YG1	3/8"	1 1/8"	53/64"	2"	BRASS
YG2	3/8"	1 1/8"	53/64"	2"	HARDENED STEEL
YG3	3/8"	1 1/8"	53/64"	2"	STAINLESS STEEL
YG5*	3/8"	1 1/8"	53/64"	2"	HARDENED STAINLESS STEEL
Y45*	3/8"	1 1/2"	53/64"	2"	HARDENED STAINLESS STEEL
Y61	3/8"	2"	53/64"	2"	BRASS
Y62	3/8"	2"	53/64"	2"	HARDENED STEEL
Y63	3/8"	2"	53/64"	2"	STAINLESS STEEL
Y65*	3/8"	2"	53/64"	2"	HARDENED STAINLESS STEEL
Y71	3/8"	3"	53/64"	2"	BRASS
Y72	3/8"	3"	53/64"	2"	HARDENED STEEL
Y73	3/8"	3"	53/64"	2"	STAINLESS STEEL
Y92	3/8"	5"	53/64"	2"	HARDENED STEEL

\* Meets or exceeds grade 6 of the ASTM F883 standards for cutting  
Key-retaining feature available for all models in this section.

**Wilson Bohannon Lock Company**

621 Buckeye Street • Marion, OH 43302 • [www.padlocks.com](http://www.padlocks.com)  
T: 800-382-3639 • F: 740-383-1653 • [wbc@padlocks.com](mailto:wbc@padlocks.com)