



Interchangeable Core Padlocks

Series 85 - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
85T5*	7.94mm	19.05mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL
8511	7.94mm	28.58mm	20.64mm	44.45mm	BRASS
8512	7.94mm	28.58mm	20.64mm	44.45mm	HARDENED STEEL
8513	7.94mm	28.58mm	20.64mm	44.45mm	STAINLESS STEEL
8515*	7.94mm	28.58mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL
85X3	7.94mm	38.1mm	20.64mm	44.45mm	STAINLESS STEEL
85X5*	7.94mm	38.1mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL
8521	7.94mm	50.8mm	20.64mm	44.45mm	BRASS
8522	7.94mm	50.8mm	20.64mm	44.45mm	HARDENED STEEL
8523	7.94mm	50.8mm	20.64mm	44.45mm	STAINLESS STEEL
8525*	7.94mm	50.8mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL
8531	7.94mm	76.2mm	20.64mm	44.45mm	BRASS
8532	7.94mm	76.2mm	20.64mm	44.45mm	HARDENED STEEL
8533	7.94mm	76.2mm	20.64mm	44.45mm	STAINLESS STEEL
8542	7.94mm	101.6mm	20.64mm	44.45mm	HARDENED STEEL

* Meets or exceeds grade 5 of the ASTM F883 standards for cutting.
Key-retaining feature available for all models in this section.

Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • www.padlocks.com
T: 800-382-3639 • F: 740-383-1653 • wbc@padlocks.com