



## Interchangeable Core Padlocks

### Series 85 - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
85T5*	5/16"	3/4"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
8511	5/16"	1 1/8"	27/32"	1 3/4"	BRASS
8512	5/16"	1 1/8"	27/32"	1 3/4"	HARDENED STEEL
8513	5/16"	1 1/8"	27/32"	1 3/4"	STAINLESS STEEL
8515*	5/16"	1 1/8"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
85X3	5/16"	1 1/2"	27/32"	1 3/4"	STAINLESS STEEL
85X5*	5/16"	1 1/2"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
8521	5/16"	2"	27/32"	1 3/4"	BRASS
8522	5/16"	2"	27/32"	1 3/4"	HARDENED STEEL
8523	5/16"	2"	27/32"	1 3/4"	STAINLESS STEEL
8525*	5/16"	2"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
8531	5/16"	3"	27/32"	1 3/4"	BRASS
8532	5/16"	3"	27/32"	1 3/4"	HARDENED STEEL
8533	5/16"	3"	27/32"	1 3/4"	STAINLESS STEEL
8542	5/16"	4"	27/32"	1 3/4"	HARDENED STEEL

\* Meets or exceeds grade 5 of the ASTM F883 standards for cutting.  
Key-retaining feature available for all models in this section.

#### Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • [www.padlocks.com](http://www.padlocks.com)  
T: 800-382-3639 • F: 740-383-1653 • [wbc@padlocks.com](mailto:wbc@padlocks.com)