



## Interchangeable Core Padlocks

### Series 86 - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
86T5*	9.53mm	19.05mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL BRASS
8611	9.53mm	28.58mm	20.64mm	50.8mm	HARDENED STEEL
8612	9.53mm	28.58mm	20.64mm	50.8mm	STAINLESS STEEL
8613	9.53mm	28.58mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL HARDENED STAINLESS STEEL BRASS
8615*	9.53mm	28.58mm	20.64mm	50.8mm	HARDENED STEEL
86X5*	9.53mm	38.1mm	20.64mm	50.8mm	STAINLESS STEEL
8621	9.53mm	50.8mm	20.64mm	50.8mm	HARDENED STEEL
8622	9.53mm	50.8mm	20.64mm	50.8mm	STAINLESS STEEL
8623	9.53mm	50.8mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL BRASS
8625*	9.53mm	50.8mm	20.64mm	50.8mm	HARDENED STEEL
8631	9.53mm	76.2mm	20.64mm	50.8mm	STAINLESS STEEL
8632	9.53mm	76.2mm	20.64mm	50.8mm	HARDENED STEEL
8633	9.53mm	76.2mm	20.64mm	50.8mm	STAINLESS STEEL
8652	9.53mm	127mm	20.64mm	50.8mm	HARDENED STEEL

\* Meets or exceeds grade 6 of the ASTM F883 standards for cutting.  
Key-retaining feature available for all models in this section.

#### Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • [www.padlocks.com](http://www.padlocks.com)  
T: 800-382-3639 • F: 740-383-1653 • [wbc@padlocks.com](mailto:wbc@padlocks.com)