



## Interchangeable Core Padlocks

### Series 86 - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
86T5*	3/8"	3/4"	27/32"	2"	HARDENED STAINLESS STEEL BRASS
8611	3/8"	1 1/8"	27/32"	2"	HARDENED STEEL
8612	3/8"	1 1/8"	27/32"	2"	STAINLESS STEEL
8613	3/8"	1 1/8"	27/32"	2"	HARDENED STAINLESS STEEL HARDENED STAINLESS STEEL BRASS
8615*	3/8"	1 1/8"	27/32"	2"	HARDENED STEEL
86X5*	3/8"	1 1/2"	27/32"	2"	STAINLESS STEEL
8621	3/8"	2"	27/32"	2"	HARDENED STEEL
8622	3/8"	2"	27/32"	2"	STAINLESS STEEL
8623	3/8"	2"	27/32"	2"	HARDENED STAINLESS STEEL BRASS
8625*	3/8"	2"	27/32"	2"	HARDENED STEEL
8631	3/8"	3"	27/32"	2"	STAINLESS STEEL
8632	3/8"	3"	27/32"	2"	HARDENED STEEL
8633	3/8"	3"	27/32"	2"	STAINLESS STEEL
8652	3/8"	5"	27/32"	2"	HARDENED STEEL

\* Meets or exceeds grade 6 of the ASTM F883 standards for cutting.  
Key-retaining feature available for all models in this section.

#### Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • [www.padlocks.com](http://www.padlocks.com)  
T: 800-382-3639 • F: 740-383-1653 • [wbc@padlocks.com](mailto:wbc@padlocks.com)